



Share:



NBRK0451



Description: Supports up to 2 external camera pods, 2 sensor pods and up to 18 Universal Sensors.
Includes : Country-specific detachable power cord , Documentation CD , Installation guide , Rack Mounting brackets , Temperature/Humidity Sensor

NetBotz Rack Monitor 450 (with 120/240V Power Supply)

Supports up to 2 external camera pods, 2 sensor pods and up to 18 Universal Sensors.

Call for More Information
04 7099333

Includes: Country-specific detachable power cord , Documentation CD , Installation guide , Rack Mounting brackets , Temperature/Humidity Sensor

Related Products, Accessories & Services

[View all accessories and replacement batteries for this product](#)



NetBotz Room Sensor Pod 155

Call for More Information
04 7099333



NetBotz Rack Sensor Pod 150

Call for More Information
04 7099333



NetBotz Device Monitoring (Five Nodes) Pack

Call for More Information
04 7099333

[Product Overview](#)

[Technical Specifications](#)

[Documentation](#)

[Software & Firmware](#)

[Options](#)

Input

[Print Technical Specification](#)

| | |
|-----------------------|-----------|
| Number of Power Cords | 1 |
| Input Power | 51.0Watts |

Physical

| | |
|-----------------|----------------|
| Maximum Height | 43mm , 4.3CM |
| Maximum Width | 432mm , 43.2CM |
| Maximum Depth | 93mm , 9.3CM |
| Rack Height | 1U |
| Net Weight | 1.74KG |
| Shipping weight | 2.86KG |
| Shipping Height | 190mm , 19.0CM |
| Shipping Width | 781mm , 78.1CM |
| Shipping Depth | 369mm , 36.9CM |

Environmental



| | |
|-----------------------------------|--|
| Operating Elevation | 0-3000meters (CE Mark, Class A, VDE Listed, UL, FCC Part 15 Class A, CECH, FCC Class II, IEC60950, IEC60950-1, IEC60950-2, IEC60950-3, IEC60950-4, IEC60950-5, IEC60950-6, IEC60950-7, IEC60950-8, IEC60950-9, IEC60950-10, IEC60950-11, IEC60950-12, IEC60950-13, IEC60950-14, IEC60950-15, IEC60950-16, IEC60950-17, IEC60950-18, IEC60950-19, IEC60950-20, IEC60950-21, IEC60950-22, IEC60950-23, IEC60950-24, IEC60950-25, IEC60950-26, IEC60950-27, IEC60950-28, IEC60950-29, IEC60950-30, IEC60950-31, IEC60950-32, IEC60950-33, IEC60950-34, IEC60950-35, IEC60950-36, IEC60950-37, IEC60950-38, IEC60950-39, IEC60950-40, IEC60950-41, IEC60950-42, IEC60950-43, IEC60950-44, IEC60950-45, IEC60950-46, IEC60950-47, IEC60950-48, IEC60950-49, IEC60950-50, IEC60950-51, IEC60950-52, IEC60950-53, IEC60950-54, IEC60950-55, IEC60950-56, IEC60950-57, IEC60950-58, IEC60950-59, IEC60950-60, IEC60950-61, IEC60950-62, IEC60950-63, IEC60950-64, IEC60950-65, IEC60950-66, IEC60950-67, IEC60950-68, IEC60950-69, IEC60950-70, IEC60950-71, IEC60950-72, IEC60950-73, IEC60950-74, IEC60950-75, IEC60950-76, IEC60950-77, IEC60950-78, IEC60950-79, IEC60950-80, IEC60950-81, IEC60950-82, IEC60950-83, IEC60950-84, IEC60950-85, IEC60950-86, IEC60950-87, IEC60950-88, IEC60950-89, IEC60950-90, IEC60950-91, IEC60950-92, IEC60950-93, IEC60950-94, IEC60950-95, IEC60950-96, IEC60950-97, IEC60950-98, IEC60950-99, IEC60950-100) |
| NOM, UL Listed, VCCI Class A, VDE | |
| Storage Temperature | -15 - 65 °C |
| Standard warranty | 2 years repair or replace |
| Storage Relative Humidity | 0 - 95 % |
| Sustainable Offer Status | |
| Storage Elevation | 0-15000meters |
| RoHS | Compliant |
| Battery Directive | Compliant |
| Battery Notes | ts_Battery_Notes |
| General | |
| Number of Additional Sensor Pods | 18.0 |



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE

CONNECT WITH US

FIND A RESELLER

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2016, APC by Schneider Electric